

RP6 ROBOT SYSTEM

RP6-BASE BOOTLOADER

DEFAULT FUSE BIT SETTINGS

©2007 AREXX Engineering



!!! WARNING !!!

**Incorrect Fuse Bit settings can
cause serious problems!**

**We created a Bootloader for user program upload
for GOOD REASONS! This makes it easier for you and you
will not run into trouble as you can not mess up the Fuse Bits.**

**If you do not have VERY GOOD REASONS to erase
the Bootloader, do not do it!**

**YOU WILL LOOSE WARRANTY IF YOU SOLDER¹ THE
ISP CONNECTOR TO THE MAINBOARD!**

Nevertheless, if you are sure that you want to erase the Bootloader
and use ISP Programming, you can still contact
our Support for assistance.

**You should use only official ATMEL Tools to program the AVR via ISP.
We recommend STK500/AVRISP along with AVRStudio.**


Better do not use Ponyprog or similar tools
if you have no prior experience with it!
The settings are very very often misunderstood in these tools!

¹ Of course you can also try to connect an ISP Connector without soldering it to the Mainboard. This may work if you only want to switch to another bootloader and back to the original one later! The Warranty will be lost if you set the Fusebits incorrectly or damage the AVR in another way. We can not give any warranties for ISP programming!

Settings for restoring the ORIGINAL BOOTLOADER

Screenshots of AVR Studio with STK500 Programmer:

1. Fuse Bits



YOU HAVE TO MAKE SURE THAT THE FUSEBIT SETTINGS ARE CORRECTLY AS FOLLOWS:

Fuse Bits Low Byte: 0xBF

Fuse Bits High Byte: 0xCA

Lock Bit Byte: (s. next page)

(All these values are hexadecimal values!)


This means that the following bits are programmed (this means set to 0!!!)

BODEN
SPIEN
CKOPT
BOOTSZ1
BOOTRST

In other words:

- Brown out detection is enabled at 2.7V
- SPI Programming is enabled (*can not be changed when using ISP Interface*)
- CKOPT is enabled
- Bootblock size is 1024 words
- Boot reset vector is enabled
- **External High frequency Crystal/Resonator is enabled with long startup time (do not change this!)**

2. Lock Bits:



Lock Bit Byte: 0xCC

This means that the following Lock Bits are programmed (set to 0!!!):

BLB12

BLB11

LB2

LB1

All other Lock Bits are unprogrammed.

In other words:

Further programming and verification is disabled

LPM and SPM are allowed in Application section

LPM and SPM are not allowed in Bootloader section

If you do not want to use the RP6 Bootloader or want to use no Bootloader at all, you may have to adjust these Settings.

You do not need to set the Lock Bits if you do not use a Bootloader and you also HAVE TO disable the Boot Reset Vector. The rest of the settings can be used as shown above. For other Bootloaders you may have to use different settings!

Always make sure that the Oscillator settings are correct! Otherwise you may not be able to program the AVR anymore and it will stop working!